



## 4651LED 4x6 Sealed High Beam

For Use as Part of a Four-Lamp Integrated System

### Product Specifications:

**Lens:** UV Protected, Hard Coated Polycarbonate Lens

**Housing:** Die Cast Aluminum, Black Powder Coated Finish

**Heat Management:** Natural Convection, Heat Fins

**Mounting:** Fixed Mounting via Mounting Pads

**Connector Type:** H4 2 Blade



**Multi-Voltage:** 9v~32v DC **Amp Draw:** 1.23a at 12.8VDC/0.52a at 28VDC

**LED's:** 8 – 3w High Output Diodes **Lumens:** 800

**Ratings & Compliances:** FMVSS 108 & CMVSS 108 Compliant

**SAE Specifications:** S14.6.15 Head Lamp Connector, S14.6.8 Vibration, S14.4.1 Color, S14.6.3 Corrosion, S14.6.4 Connector Corrosion, S6.5.3 Markings, S14.6.1 Abrasion, S14.6.2 Chemical Resistance, S14.6.5 Dust, S14.6.6.4 Internal Heat, S14.6.6.3 Temperature Cycle, S14.6.7 Humidity.

**Interchange:** Replacement for H4651

- This DOT Approved High Beam Headlight is Legal For All Four-Lamp Integrated Systems
- Lamp Can Be Used On 12v or 24v Electrical Systems
- 3-1/2" Wire Pigtail With Standard OEM 2 Blade Connector
- UV Protected Polycarbonate Lens Resists Cracking and Yellowing

**Use ProLED Headlights to Replace Your Old, Dim Halogen Lamps**