



4656LED 4x6 Sealed Low Beam

For Use as Part of a Four-Lamp Integrated System

Product Specifications:

Lens: UV Protected, Hard Coated Polycarbonate Lens

Housing: Die Cast Aluminum, Black Powder Coated Finish

Heat Management: Natural Convection, Heat Fins

Mounting: Fixed Mounting via Mounting Pads

Connector Type: H4 3 Blade



Multi-Voltage: 9v~32v DC **Amp Draw:** 0.79a at 12.8VDC/0.32a at 28VDC

LED's: 1 – 15w High Output Diode **Lumens:** 700

Ratings & Compliances: FMVSS 108 & CMVSS 108 Compliant

SAE Specifications: S14.6.15 Head Lamp Connector, S14.6.8 Vibration, S14.4.1 Color, S14.6.3 Corrosion, S14.6.4 Connector Corrosion, S6.5.3 Markings, S14.6.1 Abrasion, S14.6.2 Chemical Resistance, S14.6.5 Dust, S14.6.6.4 Internal Heat, S14.6.6.3 Temperature Cycle, S14.6.7 Humidity.

Interchange: Replacement for H4656

- This DOT Approved Low Beam Headlight is Legal For All Four-Lamp Integrated Systems
- Lamp Can Be Used On 12v or 24v Electrical Systems
- 3-1/2" Wire Pigtail With Standard 3 Blade H4 Connector
- UV Protected Polycarbonate Lens Resists Cracking and Yellowing

Use ProLED Headlights to Replace Your Old, Dim Halogen Lamps