



6024LED 7" Sealed Beam Headlight

Product Specifications:

Lens: UV Protected, Hard Coated Polycarbonate Lens

Housing: Die Cast Aluminum, Black Powder Coated Finish

Heat Management: Natural Convection, Heat Fins

Mounting: Fixed Mounting via Mounting Pads

Connector Type: Automotive H4



Multi-Voltage: 9v~32v DC **Power Draw at (12v):** Low Beam, 15W. High Beam, 27W
Low Beam Lumens: 600 **High Beam Lumens:** 1085

Ratings & Compliances: FMVSS 108 Head Lamps: 2D1

SAE Specifications: S14.6.15 Head Lamp Connector, S14.6.8 Vibration, S14.4.1 Color, S14.6.3 Corrosion, S14.6.4 Connector Corrosion, S6.5.3 Markings, S14.6.1 Abrasion, S14.6.2 Chemical Resistance, S14.6.5 Dust, S14.6.6.4 Internal Heat, S14.6.6.3 Temperature Cycle, S14.6.7 Humidity.

Interchange: Replacement for 6014, 6015, 6016, H6024 & Par 56 Headlamp Designs

- This DOT Approved 2D1 Headlamp System Is Legal For All 7" Par 56 Systems to Include Motorcycles, Passenger and Commercial Vehicles
- Lamp Can Be Used On 12v or 24v Electrical Systems
- 4-1/2" Wire Pigtail With Standard 3 Pin, H4 Connector
- UV Protected Polycarbonate Lens Resists Cracking and Yellowing

Use ProLED Headlights to Replace Your Old, Dim Halogen Lamps